

Ambiente-Uniq

Product data EN ISO 10582

	Standard	Technical data
Total thickness	EN ISO 24346	3 mm
Wear layer	EN ISO 24340	0,55 mm
Weight	ISO 23997	5 kg / m ²
Wear layer binder content	EN ISO 24342	Type 1
Size	EN ISO 24342	457,2 x 101,6 mm, 72 planks/box = 3,345 m ² 1.505 x 235 mm, 10 planks/box = 3,54 m ² 914,4 x 457,2 mm, 8 tiles/box = 3,34 m ²
Classification		
European classification	EN ISO 10874	Class 33-42
Fire resistance	EN-13501	B _{fl} -S1
Electrical resistance	EN-1815	< 2 kV
Slip resistance	DIN 51130	R9 / R10 depending on embossing
Technical Features		
Sound Absorption	EN-ISO-717-2	ΔLw = 6 dB
Dimensional stability	EN ISO 23999	≤ 0,10 %
Residual Indentation	EN ISO 24343-1	≤ 0,10 mm
Underfloor heating		Suitable - max. 27 °C
Castor chair	ISO 4918	Suitable
Chemical resistance	EN ISO 26987	Not affected
Thermal resistance	EN ISO 10456	0,02 m ² K/W
Light fastness	EN ISO 105 – B02	≥ 6
Coating		PU
CE Mark		



EN-14041

