


Contract-Click

Product data EN ISO 10582

	Standard	Technical data
Total thickness	EN ISO 24346	5 mm
Wear layer	EN ISO 24340	0,55 mm
Weight	ISO 23997	7,8 kg / m ²
Click connection	Length / Width	2G Valinge
Wear layer binder content	EN ISO 24342	Type 1
Size	EN ISO 24342	1.211,2 x 169,8 mm ⁽¹⁾ 601,6 x 296,8 x mm ⁽²⁾
Locking system		Click Välinge 2G
Classification		
European classification	EN ISO 10874	Class 33-42
Fire resistance	EN-13501	B _{fl} -S1
Electrical resistance	EN-1815	< 2 kV
Slip resistance	DIN 51130	R10
Technical Features		
Sound Absorption	EN-ISO-717-2	ΔLw = 19 dB
Dimensional stability	EN ISO 23999	≤ 0,10 %
Residual Indentation	EN ISO 24343-1	≤ 0,10 mm
Underfloor heating		Suitable - max. 27 °C
Castor chair	ISO 4918	Suitable
Chemical resistance	EN ISO 26987	Not affected
Thermal resistance	EN ISO 10456	0,05 m ² K/W
Light fastness	EN ISO 105 – B02	≥ 6
Coating		PU
Packaging units		
10 planks ⁽¹⁾ 2,057 m ² / Box	60 Boxes / Pallet	123,42 m ² / Pallet
12 tiles ⁽²⁾ 2,142 m ² / Box	60 Boxes / Pallet	128,52 m ² / Pallet
CE Mark		
	EN-14041	