


Contract-Lock

Product data EN ISO 10582

	Standard	Technical data
Total thickness	EN ISO 24346	5 mm
Wear layer	EN ISO 24340	0,7 mm
Weight	ISO 23997	8 kg / m ²
Wear layer binder content	EN ISO 24342	Type 1
Size	EN ISO 24342	457,2 x 457,2 mm
Classification		
European classification	EN ISO 10874	Class 34-43
Fire resistance	EN-13501	B _{fl} -S1
Electrical resistance	EN-1815	< 2 kV
Slip resistance	DIN 51130	R10
Technical Features		
Sound Absorption	EN-ISO-717-2	ΔLw = 12 dB
Dimensional stability	EN ISO 23999	≤ 0,15 %
Residual Indentation	EN ISO 24343-1	≤ 0,10 mm
Underfloor heating		Suitable - max. 27 °C
Castor chair	ISO 4918	Suitable
Chemical resistance	EN ISO 26987	Not affected
Thermal resistance	EN ISO 10456	0,05 m ² K/W
Light fastness	EN ISO 105 – B02	≥ 6
Coating		PU
Packaging units		
10 tiles 2,09 m ² / Box	60 Boxes / Pallet	125,40 m ² / Pallet
CE Mark		
	EN-14041	